

Driver		Date		Track		Event		Spur Gear		Pinion Gear	
								<input type="checkbox"/> 46T(Std.) <input type="checkbox"/> 47T <input type="checkbox"/> 48T		T	
		Condition :									
Motor		Battery		ESC		Tires		Tire Insert		Wheel	
				Compound :							

● Diff. Gear Set-Up

	Front		Center		Rear	
Diff. Gear	<input type="checkbox"/> Std.	<input type="checkbox"/> LSD	<input type="checkbox"/> Std.	<input type="checkbox"/> LSD	<input type="checkbox"/> Std.	<input type="checkbox"/> LSD
	<input type="checkbox"/> IFW621		<input type="checkbox"/> IFW622		<input type="checkbox"/> IFW621	
	Ring Gear	#	#	#	Ring Gear	#
	<input type="checkbox"/> 43/13				<input type="checkbox"/> 43/13	
	<input type="checkbox"/> 42/12				<input type="checkbox"/> 42/12	

● Shock Set-Up

	Front		Rear	
Shock Type	P : w/Diaphragm A : Aeration		Size	type
Shock Piston	φ		φ	
Shock Oil	#		#	
Shock Spring	Length	Color	Length	Color

● Ride Height

Front	Rear
mm	mm

● Rebound

Front	Rear
mm	mm

● Camber Angle

Front	Rear
+ °	+ °
- °	- °


● Toe Angle

Front	Rear
+ °	<input type="checkbox"/> 2.5° <input type="checkbox"/> 3° <input type="checkbox"/> 3.5°
- °	

● Wheelbase

Collar of Rear Hub	Front Side _____ mm
	Rear Side _____ mm

● Shock Mount Position



Shock Stay

Front	<input type="checkbox"/> Std. <input type="checkbox"/> Long
Rear	<input type="checkbox"/> Std. <input type="checkbox"/> Long


Rear Upper Shock Bush

<input type="checkbox"/> Std. <input type="checkbox"/> Long

Sus. Arm

Front	<input type="checkbox"/> In <input type="checkbox"/> Out
Rear	<input type="checkbox"/> In <input type="checkbox"/> Out

● Rear Upper Arm Position



<input type="checkbox"/> Plastic
<input type="checkbox"/> Aluminum

Hub Carrier Bush	<input type="checkbox"/> Plastic <input type="checkbox"/> Brass
------------------	---

● Rear Wheel Hub

<input type="checkbox"/> Narrow <input type="checkbox"/> Std. <input type="checkbox"/> Wide


● Front Sus. Arm

<input type="checkbox"/> Soft (Std.)	<input type="checkbox"/> Hard
--------------------------------------	-------------------------------

● Front Sus. Bush

Rear Side	
-----------	--

● Front Upper Arm Position




● Front Wheel Hub

<input type="checkbox"/> Narrow <input type="checkbox"/> Std. <input type="checkbox"/> Wide

● Front Hub Carrier

<input type="checkbox"/> Plastic <input type="checkbox"/> Aluminum
<input type="checkbox"/> 13° <input type="checkbox"/> 16° <input type="checkbox"/> 17.5° <input type="checkbox"/> 19°



● Front Wheel Hub

Lower Bush	<input type="checkbox"/> Plastic <input type="checkbox"/> Brass
-1°	0° +1°

● Rear Sus. Bush

Front Side	
Rear Side	


● Rear Sus. Arm

<input type="checkbox"/> Soft (Std.)	<input type="checkbox"/> Hard
Rear Sus. Bush	
Short	
Medium	
Long	


● Servo Horn

Steering	Throttle
<input type="checkbox"/> Plastic	<input type="checkbox"/> Plastic
<input type="checkbox"/> Alum. Long	<input type="checkbox"/> Aluminium
<input type="checkbox"/> Alum. Short	

● Steering Plate



● Sway Bar



Front	Rear
φ	φ
mm	mm

● Weight

Front	Rear
<input type="checkbox"/> None	<input type="checkbox"/> None
<input type="checkbox"/> IFW604-10	<input type="checkbox"/> IFW605-10
<input type="checkbox"/> IFW604-20	<input type="checkbox"/> IFW605-20
<input type="checkbox"/> other	<input type="checkbox"/> other

● Wing

<input type="checkbox"/> IF491(TK14)	Flap	<input type="checkbox"/> None
		<input type="checkbox"/> 5mm
		<input type="checkbox"/> 8mm
		<input type="checkbox"/> Holes

Am0 - Peltric.com

Notes